

XRpad2 3025



Flat Panel X-ray Detectors

Features and Benefits

- 25 cm × 30 cm (10" × 12") image
- High resolution 100 μm pixel pitch (5.0 lp/mm)
- Direct deposition CsI, for excellent image quality
- Up to 65,536 grey levels (16-bit ADC)
- Automatic Exposure Detection (AED)
- Wi-Fi interface (Station and Access Point modes)
- Docking connector for GigE, power and sync
- On-board pixel corrections and storage
- Dynamic mode for tomosynthesis
- Fast preview image
- Robust and lightweight design

Applications¹

- Digital radiography

Digital Radiography and Beyond

Overview

XRpad2 3025 is a lightweight wireless cassette detector with advanced features enabling digital radiography as never seen before.

Featuring best-in-class 100 μm pixel size, direct deposition CsI scintillator and excellent DQE, XRpad2 3025 enables high resolution imaging with reduced X-ray exposure. Design of the second-generation XRpad® is lightweight, robust and ergonomic, permitting easy lifting from table top. Automatic Exposure Detection, on-board corrections, and wireless access point mode make system integration quick and simple.

New features of the XRpad2 3025 include fast preview, internal image storage, and magnetic connector for docking. Continuous imaging at up to 10 fps facilitates advanced applications such as tomosynthesis, dual energy subtraction, and image stitching.

PerkinElmer Medical Imaging has partnered with OEM customers for more than 25 years to develop products for a wide range of X-ray applications. Let our digital imaging expertise work for you.

XRpad2 3025

Sensor	
Panel	Amorphous silicon active TFT-diode array
Scintillator	Direct deposition CsI:Tl
Pixel Matrix	2508 × 3004
Pixel Pitch	100 µm
Electronics	
Amplifiers	Low noise ASICs with user selectable gains
ADC	16-bit
Image Transfer Time	Wired: 300 ms; Wireless: 2000 ms
On-board Memory	1 GB DDR3, 8 GB SDHC card
Mechanical	
Size	ISO 4090 for 25 cm × 30 cm (10" × 12") cassette size
Active Area	248.0 mm × 297.6 mm
External Dimensions	282 mm (w) × 332 mm (l) × 15.5 mm (h)
Weight	1.8 kg (4 lbs)
Housing	Aluminum frame with carbon-fiber entrance window
Communications	
Status Display	OLED display with Wi-Fi, LAN, battery, and sensor indicators
Wireless Data I/F	802.11n Wi-Fi standard at 5 GHz
Wired Data I/F	GigE, trigger and power via docking connector
X-ray I/F	Integrated X-ray trigger control / Automatic Exposure Detection


Imaging Performance	
Typical DQE	75% (0 cy/mm), 60% (1 cy/mm), 40% (3 cy/mm) for RQA5
Typical MTF	70% (1 cy/mm), 40% (2 cy/mm), 15% (4 cy/mm) for RQA5
Limiting Resolution	5 cy/mm
Advanced Features	
Dynamic Mode ²	10 fps at 200 µm resolution
On-board Corrections	Offset, gain and defective pixel
On-board Storage	Image storage with tagging
Fast Preview	4 × 4 binned quick preview image
Environmental	
Temperature	10 °C to 35 °C operating
Humidity	20% to 80% operating
Ingress Protection	IPX4 rated (protection against splashing water)
Accessories	
Battery	Rechargeable battery, 11.1 V
Battery Charger	External two bay charger 100 - 240 V AC, 50/60 Hz
Interface and Power Unit	Optional IPU-2 external power supply 100 – 240 V AC 50/60 Hz GigE and X-ray I/F
Regulatory	
Standards	EN 60601-1:2006+AC:2010, EN 60601-1-2:2015, FCC part 2 subpart J, FCC part 15 subpart B/C/E, ETSI EN 301 893 V.1.7.1 (2012), ETSI EN 301 489-1 V1.9.2 (2011), ETSI EN 301 489-17 V2.2.1 (2012), EN ISO 10993-5:2009, EN ISO 10993-10:2010

¹ Unless otherwise specified, PerkinElmer Flat Panel X-ray Detectors are components intended to be integrated into products by X-ray system manufacturers. System manufacturers are responsible for qualifying and validating their products for their intended uses and meeting all applicable regulatory requirements.

² Not intended for fluoroscopy applications

Contents in this document are subject to change without notice.

Mechanical Characteristics (Dimensions in mm)



Visit our website at www.perkinelmer.com/imaging-components/ and contact us through the contact form provided or email fpd@perkinelmer.com.

USA
PerkinElmer Inc.
2175 Mission College Blvd
Santa Clara, CA 95054 USA
P: +1-844-726-8228
F: +1-408-969-6493

Germany
PerkinElmer
Technologies GmbH & Co. KG
In der Rehbach 22
65396 Walluf Germany
P: +49-6123-971-300
F: +49-6123-971-600

United Kingdom
Dexela Limited
A PerkinElmer Company
Wenlock Business Centre
50-52 Wharf Road
London N1 7EU United Kingdom
P: +44-20-7148-3107

China
PerkinElmer, Inc.
No. 1670 Zhangheng Road
Zhangjiang Hi-Tech Park
Shanghai 201203, PRC
P: +86-21-60645611
F: +86-21-60645666



For a complete listing of our global offices, visit www.perkinelmer.com/ContactUs

Copyright ©2012-2017, PerkinElmer, Inc. All rights reserved. PerkinElmer® is a registered trademark of PerkinElmer, Inc. All other trademarks are the property of their respective owners.